

HOW TO CREATE YOUR PART NUMBER

XXXX	X	XXX	XXX	XX	XX
PRODUCT	VERSION (IF APPLICABLE)	SIZE (IF APPLICABLE)	COLOUR	LENS (IF APPLICABLE)	OPTIONS
EBAR MBACK MR HPRING etc.	STANDARD O OVERDRIVE L LINK E EXPERT etc.	125 250 375 500 etc.	WHI 630 470 850 etc.	7 ± 7° 10 ± 10° 9-16 ± 9°/16° 17 ± 17° etc.	DIFFUSERS DO, DS, DT POLARIZER POL MR ACCESSORIES D, DF, LA PROTECTION IP65, IP69K WIRING, etc.

PART NUMBER EXAMPLES :

EBAR+ Link 250mm Red LED ±17° ➔ **EBAR-L-250-630-17**
MBACK+ Overdrive 80x50cm Red LED Connector M12 ➔ **MBACK-O-8050-630-M1**
MODULAR RINGLIGHT 130mm Red & Cyan LED Dome version ➔ **MR-130-RC-D**
HPRING White LED ±10° Opaque diffuser ➔ **HPRING-WHI-10-DO**



LED ILLUMINATION FOR MACHINE VISION

TPL VISION CONTACTS

TPL Vision UK

TPL Vision PL

TPL Vision FR
Manufacturing

TPL Vision HK

Caroline WINN
VP OF SALES
Worldwide
+44 (0)7340 367 871
cwinn@tpl-vision.co.uk
Spoken language:

Pawel GARBOWICZ
EXECUTIVE SALES
Germany & Eastern Europe
+44 (0)7470 643 241
pgarbowicz@tpl-vision.co.uk
Spoken language:

Martin HENDERSON-BLUNN
TECHNICAL SALES EXECUTIVE
Europe
+44 (0)1738 310 392
mhenderson@tpl-vision.co.uk
Spoken language:

Amanda McCLINTOCK
CUSTOMER SERVICE OFFICER
Europe
+44 (0)1738 310 392
amcclintock@tpl-vision.co.uk
Spoken language:

STANDARD



EBAR+



BLBAR+



LBAR+



EBAR CURVE



XBAR RGB

LINK



EBAR+ LINK



BLBAR+ LINK

OVERDRIVE



EBAR+ OVERDRIVE



BLBAR+ OVERDRIVE



EBAR LOGISTIX



MBACK+ OVERDRIVE



Collimated CMBACK+ OVERDRIVE



Bn'L (Black & Light) OVERDRIVE



MR - MODULAR RINGLIGHT



FLOOD LIGHT



MR - DOME



MR - DARK FIELD

EXPERT




EBAR+ EXPERT



BLBAR+ EXPERT



MBACK+ EXPERT



CMBACK+ EXPERT



Bn'L EXPERT



MFDOME+ EXPERT

FOOD



EBAR FOOD



BLBAR FOOD

ADD-ONS



OPTICAL TRIGGER



DIFFUSER



POLARIZER



FILTERS



MOUNTING



CABLES



SAFETY GLASSES

LEGEND

- White WHI

Red 630nm

Green 525nm

Blue 470nm

Infrared

RGB

White-Infrared

Red-Cyan

Ultraviolet 405nm

Ultraviolet 365nm

Ultraviolet 385nm

No current control inside
- 65 IP65 by default

66 IP66 by default

69K IP69K by default

65 Optional: IP65

66 Optional: IP66

69K Optional: IP69K